



## **SYNTHETIC GEAR OIL API GL-5 - 75W-90**

### **Technical Data Sheet**

#### **Ultimate Protection for the latest low-emission engines**

LUBCAN 75W/90 Full Synthetic Gear Oils are formulated with synthetic base oils and premium gear additive packages to provide improved high-temperature thermal and oxidative stability in a wide range of operating conditions and advanced protection and lubricity in extreme pressure conditions.

#### **Performance Specifications / Standards**

- API GL-5
- Mack GO-J Plus
- API MT-1
- SAE J2360
- ZFTE-ML07A
- MIL-L-2105D
- MIL-PRF-2105E
- Scania STO 1:

#### **Performance Features & Benefits**

- Formulated with synthetic base oils and a premium gear additive package
- Formulated to provide improved high-temperature thermal and oxidative stability in a wide range of operating conditions
- Provides advanced protection and lubricity in extreme pressure conditions
- Highly shear stable while also resisting rust, oxidation, foaming, and varnish
- Designed to exceed the year-around, all-weather performance viscosity requirements of SAE J306 as well as the rigorous performance requirements of API GL-5
- Protects the combination of thermal degradation, component wear, and oil seal deterioration

#### **Typical Physical Characteristics**

<b>SAE Viscosity Grade</b>	<b>75W-90</b>
Appearance	0.885
Viscosity @ 40°C, cSt	114.3
Viscosity @ 100°C, cSt	15.1
Viscosity Index	138
Flash Point, COC, °C	216